

State of Louisiana
Department of Transportation and Development

Qualified Products List 24

RAPID SETTING PATCHING MATERIALS FOR CONCRETE*

PRODUCT SOURCE CODE	PRODUCT	ONE SACK MIX DESIGN	MAXIMUM PLACEMENT TIME**	SOURCE
(A) CEMENTITIOUS PATCHING MATERIALS				
2439	Pave Patch 3000	Pave Patch Water Approx. Yield	23 kg (50 lb.) <u>2.8 L (3 qt.)</u> .012 m ³ (0.41 cu. ft.)	20 minutes Conspec Marketing & Mfg. 4226 Kansas Avenue Kansas City, KS 66106
2436	Rapid Set Concrete Mix	Rapid Set Water Approx. Yield	27 kg (60 lb.) <u>2.4 L (2.5 qt)</u> .014m ³ (0.5 cu. ft.)	20 minutes CTS Cement Mfg. Company 11065 Knott Avenue Suite A Cypress, CA 90630
2425	Euco-Speed	Euco-Speed Water Approx. Yield	23 kg (50 lb.) <u>2.8 L (3 qt.)</u> .011 m ³ (0.41 cu. ft)	15 minutes Euclid Chemical Company 19320 Redwood Road Cleveland, OH 44110-2799
2431	Speed Crete Green Line	Speed Crete Water Approx. Yield	23 kg (50 lb.) <u>3.8 L (1 gal.)</u> .014 m ³ (0.5 cu. ft)	
2418	Durapatch Hiway	Durapatch Water Approx. Yield	23 kg (50 lb.) <u>2.4 L (2.5 qt.)</u> .012 m ³ (0.42 cu. ft)	10 minutes L & M Const. Chemicals 14851 Calhoun Road Omaha, NE 68152
2423	Transpo** Polymer Concrete (Transpo T17)	Transpo T17 Activator Soln. Approx. Yield	14 kg (30 lb.) <u>1.89 L (½ gal.)</u> .007 m ³ (0.25 cu. ft)	20 minutes Transpo Industries, Inc. 20 Jones Street New Rochell, NY 10801
2441	Futura 15	Futura 15 Water Approx. Yield	23 kg (50 lb.) <u>2.48 L (2.6 qt.)</u> 0.012 m ³ (0.43 ft ³)	15 minutes W. R. Meadows, Inc. 2555 N. E. 33 rd Street Fort Worth, TX 76111
(B) THERMOPLASTIC PARTIAL DEPTH CONCRETE PAVEMENT PATCHING MATERIALS				
No approved sources				

**The products included in this list are intended for maintenance repairs of portland cement concrete pavements and bridge decks. Some of these products contain activators which may result in flash set during hot weather applications, thereby requiring precautionary measures to be taken in accordance with the manufacturer's instructions.*

***Varies with temperature*

NOTE:

Any patching material on this list may be used without sampling and pretesting provided it is properly identified as being the specific material on the list. However, sampling and testing before use may be required whenever a product is questionable for any reason.

Any deviation in composition or performance from the original sample submitted may result in removal of the product from the qualified list.

No information contained in this list is to be used for promotional purposes.